TOOLBOXTOPICS.COM

Company Name	Job Name	Date
	HAND SIGNALS FOR CRANE OPERA	ATIONS
special operations may require can see you and that both of y	nmonly used hand signals for directing crane adaptations of these basic signals. When us ou understand all the signals. You and the ors lives depend on your skills. A wrong signal!	sing hand signal be sure the operato operator are in charge of an
HOIST Extend the right arm move hand in small horizontal	straight out and raise the forearm to vertica circle.	al, forefinger pointing up, then
OWER Extend the right arm	n downward, forefinger pointing down, then	move hand in small horizontal circle
RAISE BOOM Extend right a	rm straight out, fingers closed and thumb po	pinting upward.
OWER BOOM Extend right	arm straight out, fingers closed and thumb p	pointing downward.
SWING Extend right arm aw	ay from body, point with finger in direction o	of swing of boom.
STOP Right arm extended do	own with wrist bent and palm down and ope	en.
EMERGENCY STOP Right arn	n extended, palm down, then move hand rap	pidly right and left.
•	r cranes only) Use both fists in front of body ction of travel - forward or backward.	, making a circular motion about
OOG EVERYTHING Clasp har	nds in front of the body.	
RAISE BOOM & LOWER LOAD as load movement is desired.	Extend right arm with thumb pointing up,	then flex fingers in and out as long
OWER BOOM & RAISE LOAD ong as load movement is desir	Extend right arm with thumb pointing dow red.	vn, then flex fingers in and out as
	o, stay alert when working near any crane op e counter balance and always remember the your own safety.	

KEEP ALL PARTS OF A CRANE, FALL LINES, HOOK, BLOCK, AND LOAD A MINIMUM OF 15 FEET FROM ALL ELECTRICAL LINES.

Job Specific

Safety

Recommendations:_____

and Signals for Crane Operations	
ics:	
.D.S iewed:	
ended By:	